

Maintenance kit for porous sandstone and limestone.

Contains:

C1.07 DAY, T3.31H, F5.21, microfiber cloth, anti-scratch sponge, gloves, paper cloth.

MATERIALS

- Marble
- Natural stone

APPLICATION FIELDS

- Cladding (walls/floors)
- Kitchen countertops
- Bathroom countertops
- Tables



FEATURES

- C1.07 DAY – detergent with pH 7, for regular use
- T3.31H – anti-stain, protects against staining substances such as oil, coffee, grease, wine, etc.
- F5.21 – anti-dirt, covers surface irregularities, preventing dirt from settling in the pores
- Organic products
Kit suitable for all highly absorbent surfaces, with rough, sandblasted, natural-split, bush-hammered finishes.

INSTRUCTIONS

SHAKE BEFORE USE

Ready-to-use products.

Spray C1.07 DAY on the surface to be cleaned and rub with the sponge.

On clean, dry surfaces, apply T3.31H, spreading evenly with a microfiber cloth, in crisscross layers. Depending on the absorbency of the surface, apply the second layer 4–6 hours after the first. Repeat the maintenance operation when the surface begins to absorb water again when wet.

On clean and dry surfaces apply F5.21, spreading evenly with a microfiber cloth, in crisscross layers. Depending on the absorbency of the surface, apply a second layer

PACKAGING

- Composed kit of bottles of 0.25 Lt/Kg

-
-

WARNINGS

Apply at an ambient temperature between 10°C and 20°C. Keep out of reach of children. Do not disperse in the environment. Before use, consult the safety data sheet and label, which highlights the risks and safety measures for the correct use of personal protective equipment.

All information contained on this page is based on data we believe to be reliable; however, not knowing the conditions of the treated materials and how you will use the product, ITALIAN XS declines any responsibility regarding the suitability of the material for each particular application.

Keep the product in its original, tightly closed containers. Store the product at a temperature between 5°C and 20°C. If stored as directed, the product will keep for months. may above, has a term of validity of 12

It is recommended to carry out preliminary tests on small areas, as our liability is limited to the cost of the product. We assume no liability for damage caused by negligence or incorrect use of the product.